(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 22 April 2004 (22.04.2004)

PCT

(10) International Publication Number WO 2004/033039 A1

(51) International Patent Classification7:

A61N 5/04

(21) International Application Number:

PCT/GB2003/004082

(22) International Filing Date:

15 September 2003 (15.09.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0223564.6

10 October 2002 (10.10.2002) GB

(71) Applicant (for all designated States except US): MICRO-SULIS LIMITED [GB/GB]; Microsulis House, Parklands Business Park, Denmead, Hampshire PO7 6XP (GB).

- (72) Inventor; and
- (75) Inventor/Applicant (for US only): CRONIN, Nigel [GB/GB]; 14 Englishcombe Lane, Bath BA2 2ED (GB).
- (74) Agents: HOGG, Jeff, K. et al.; Withers & Rogers, Goldings House, 2, Hays Lane, London SE1 2HW (GB).


- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: MICROWAVE APPLICATOR



(57) Abstract: A microwave applicator comprising a coaxial electrical input (4) and a waveguide (1) filled with dielectric (2), an inner conductor (7) of the coaxial input extending longitudinally within one end of the waveguide to launch microwaves in the TMo1 mode to travel to the distal end face (8) of the waveguide so that microwaves are transmitted when the distal end face is contacted by the biological tissue to be treated.



